



Security Tech Germany

nothingbut

www.PADLOCKS.co.uk

OCCUPATIONAL SAFETY

**LOCKOUT / TAGOUT
WITH SYSTEM**

Is your company ready for LoTo?



Areas of Application

Plug lockouts prevent electrical plugs from being inserted into a wall outlet, for use when a plug will not remain under the exclusive control of the person performing service or maintenance.

Details


- High-quality polypropylene: long-lasting, robust and non-conductive
- 2 Sizes: For standard household plugs or high-voltage plugs
- Cable tunnel on both sides to secure plug connections
- Warning stickers in different languages (English, French, Spanish) included
- Holds up to 2 padlocks (P110) resp. 4 padlocks (P550)
- Fire resistance: UL Rating UL 94 – HB

Material

- Body: Polypropylene

Dimensions

Item	Width (A):	Length (B):	Inner length (E):	Inner height (D):	Ø Cable	Ø Padlock
					tunnel (C):	insert (F):
					max.	max.
P110	80.0 mm	88.9 mm	81.3 mm	43.2 mm	12.4 mm	9 mm
P550	117.1 mm	177.8 mm	169.3 mm	75.9 mm	26.0 mm	9 mm



Temperature Range

- Polypropylene: -20° to 80°C (0° to 175°F)

Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only. The results were determined at a room temperature of +20°C/+68°F. All data are subject to environmental variables and product features.

Chemical	Grade
Mineral lubricants	Conditionally resistant
Aliphatic hydrocarbons	Conditionally resistant
Aromatic hydrocarbons	Conditionally resistant
Gasoline	Conditionally resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Conditionally resistant
Strong organic acids	Conditionally resistant
Oxidizing acids	Conditionally resistant
Weak bases	Resistant
Strong bases	Resistant
Trichloroethylene	Conditionally resistant
Perchloroethylene	Conditionally resistant
Acetone	Resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Resistant
UV light and weather	Conditionally resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.

P110 / P550 | Plug Lockout User Manual



Security Tech Germany

Material Content:

a. Plug Lockout Small P110

b. Self-adhesive Label



a. Plug Lockout Large P550

b. Self-adhesive Label

P110:

- For standard 110/220V power plugs
- Cable diameter: 12 mm (0,5")
- Inner diameter: 42 mm (3,5")

P550:

- For standard power plugs up to approx. 550V
- Cable diameter: 25 mm (1")
- Inner diameter: 74 mm (7")

Application:



1.

1. Remove the plug from the socket. Open the plug lockout device and insert the plug inside with the cable in the cable opening.



2.

2. Close the plug lockout device.



3.

3. Insert at least one padlock into one of the holes provided and lock it.
4. Check whether the plug is securely locked by pulling on the cable.
5. If the plug can be pulled out through the side opening of the cable, the selected lock device is not suitable for the plug. In this case, please use the smaller size (see above).



Please note that the P110 and P550 plug lockout device may also be suitable for other plug types such as compressed air plugs or hose connections. It is important in this case that the plug or connection cannot be pulled through the side opening of the device. It should remain securely locked in the lock device.

WARNING:



Product should only be used by personnel properly trained in lockout procedures. Product should only be used on the appropriate application (s). Follow product instructions for proper application of each product. Properly trained personnel should check to ensure that product is secure and equipment will not operate. Failure to follow product instructions and warnings may result in serious bodily injury or death.

You will find additional notes and corresponding application videos to every lockout device following the link:
<http://www.abus.com/eng/Service/Videos/Industrial-safety>